

Comparison showcase fittings 1/2







Vitris offers a comprehensive, modular system of high quality all-glass sliding door fittings for showcases, furniture and serving hatches, including the appropriate locks:

Supra is a well-designed, bottom running glass sliding door fitting that is suitable for use with glass thicknesses of 4, 5, 6 and 8 mm and sash weights of up to 50 kg. Supra can also be used for single and multiple track solutions or for solutions with all-round frames.

Robustus is the showcase and furniture fittings solution for thick glass and therefore also suitable for high sashes. Robustus can be used for all glass thicknesses of 8, 10, 12 and 12.76 mm. Robustus roller assembly technology enables loads of up to 140 kg.

Penda/Bipenda is a single track (Penda) and twin track (Bipenda) hanging sliding door system which is suitable for glass thicknesses up to 8 mm and sash weights up to 50 kg. It is ideal for all applications requiring a base without fittings or that cannot be machined (e.g. serving hatches, public counters, parquet flooring).

Dura/Durus is a gliding fittings system for glass thicknesses up to 4 mm (Dura) or 6 mm (Durus) which is suitable for lightweight sashes. The sashes glide on colour-coordinated plastic inserts.

	Supra	Robustus	Penda/Bipenda	Dura/Durus
Type of fitting	Bottom running glass sliding door fitting	Bottom running glass sliding door fitting	Hanging sliding fitting	Simple gliding fitting
	 SUPRA	 ROBUSTUS	 PENDA BIPENDA	 DURA/ DURUS
Suitable glass thicknesses	4 mm, 5 mm, 6 mm, 8 mm	8 mm, 10 mm, 12 mm, 12,76 mm	Up to 8 mm	Dura: up to 4 mm Durus: up to 6 mm
Maximum sash weight:	25 kg (2 rollers) 50 kg (4 rollers)	70 kg (2 rollers) 140 kg (4 rollers)	25 kg (2 rollers) 50 kg (4 rollers)	For lightweight sashes
Available colour options	Natural aluminium EV1; stainless steel anodized C31; gold EV3	Natural aluminium EV1; stainless steel anodized C31	Natural aluminium EV1	Natural aluminium EV1

Product descriptions, drawings and illustrations represent neither assured characteristics nor declarations of guarantee. Subject to change.

	Supra	Robustus	Penda/Bipenda	Dura/Durus
Number of possible tracks	Single track, twin track or multi-track systems	Twin track system	Penda: single track system; Bipenda: twin track system	Twin track system
Availability of a frame profile	Horizontal and vertical frame profile	Vertical frame profile	None	None
Appropriate Secura locks	Secura roller profile lock with appropriate adapter; Security glass door lock with L-cam that grips around the second sash	Secura roller profile lock with appropriate adapter	Security glass door lock with locking latch in lower guide (up to 6 mm glass thickness)	
Other available accessories	<ul style="list-style-type: none"> • End plate notched • Finger pull handle • Bedding profiles • Dust protection and damper profile for frame profile • Slip-on bristle linings • Vibration damper with anti-theft device • Damping device and anti-theft device 	<ul style="list-style-type: none"> • End plate notched • Finger pull handle • Bedding profile • Dust protection and damper profile for frame profile • Slip-on bristle linings • Damping device and anti-theft device 	<ul style="list-style-type: none"> • End plate • Damping device • Lower guide for sash 	

Product descriptions, drawings and illustrations represent neither assured characteristics nor declarations of guarantee. Subject to change.